



Submersible Sewage Grinder Pump 1300 Watt 240 Volt

- Very Powerful Sewage Sump Pump
- Quality Cast Iron and Stainless Steel
- Quality Grinder Cutting Mechanism
- Power rating 1.3KW (1300 watt) 240 volt
- 50mm discharge outlet...
- Flow rate 310L/per min...12 meter max head.
- Product GW, 25kg.
- Adjustable float height, auto start.
- Extra long top quality power cable 5.5mt

[Read More](#)

SKU: SPC1300

Price: £300.00 Inc. VAT

Categories: [Sewage Grinder Pumps](#), [Sewage Sump Pumps and Pumping Stations](#)

Product Description

Ideal for pumping stations suitable for 200L to 1000L plus tank combination. Will extract waste from a combination, Toilet, shower, bath, basin etc. Super Powerful Submersible Grinder sewer waste pump constructed of high quality stainless steel and cast iron. Steel macerating mechanism. The pump can withstand harsh environments. The 1300 series is submersible to a depth of 5 meters and can withstand temperatures of up to 40deg C. The 1300 watt pump is capable of evacuating Slurry and sludge with solid particles up to 20mm when macerated. Power rating 1.3KW (1300 watt)...240 volt 50mm discharge outlet...Flow rate 310L/per min...12.0 meter max head. Product GW, 25kg...Dimension, packing size50.0 x 26.0 x 21cm. Adjustable float height, auto start. Extra long top quality power cable 5.5mt



Submersible Sewage Grinder Pump 750 Watt 240 Volt

- Powerful Sewage Sump Pump
- Quality Cast Iron and Stainless Steel
- Quality Grinder Cutting Mechanism
- Power rating 0.75KW (750 watt) 240 volt
- 40,50mm discharge outlet...
- Flow rate 205L/per min...9 meter max head.
- Product GW, 18kg.
- Adjustable float height, auto start.
- Extra long top quality power cable 5.5mt

[Read More](#)

SKU: SPC750

Price: £238.80 Inc. VAT

Categories: [Sewage Grinder Pumps](#), [Sewage Sump Pumps and Pumping Stations](#)

Product Description

Ideal for pumping stations suitable for 100L to 500L plus tank combination. Will extract waste from a combination, Toilet, shower, bath, basin etc. Powerful Submersible Grinder sewer waste pump constructed of high quality stainless steel and cast iron. Steel macerating mechanism. The pump can withstand harsh environments. The 750 series is submersible to a depth of 5 meters and can withstand temperatures of up to 40deg C. The 750 watt pump is capable of evacuating Slurry and sludge with solid particles up to 20mm when macerated. Power rating 0.75KW (750 watt)...240 volt 40,50mm discharge outlet...Flow rate 250L/per min...9.0 meter max head. Product GW, 18kg...Dimension, packing size 26.0 x 20.0 x 49cm. Adjustable float height, auto start. Extra long top quality power cable 5.5mt



Submersible Sewage Grinder Pump 370 Watt 240 Volt

- Sewage Sump Pump
- Quality Cast Iron and Stainless Steel
- Grinder Cutting Mechanism
- Power rating 0.37KW (370 watt) 240 volt
- 40,32mm discharge outlet...
- Flow rate 140L/per min...7 meter max head.
- Product GW, 11kg.
- Adjustable float height, auto start.
- Extra long top quality power cable 5.5mt

[Read More](#)

SKU: SPC370

Price: £198.00 Inc. VAT

Categories: [Sewage Grinder Pumps](#), [Sewage Sump Pumps and Pumping Stations](#)

Product Description

Ideal for pumping stations suitable for 100L to 400L plus tank combination. Will extract waste from a combination, Toilet, shower, bath, basin etc. Powerful Submersible Grinder sewer waste pumps are constructed of high quality stainless steel and cast iron. Steel macerating mechanism. The pump can withstand harsh environments. The 370 series is submersible to a depth of 5 meters and can withstand temperatures of up to 40deg C. The 370 watt pump is capable of evacuating Slurry and sludge with solid particles up to 20mm when macerated. Power rating 0.37KW (370 watt)..240 volt 40,32mm discharge outlet...Flow rate 140L/per min...7.0 meter max head. Product GW, 11kg...Dimension, packing size 18.0 x



Commercial Grade Sewage Sump Pump Wqasd7 16-1-2

Commercial Grade Sewage sump pump WQAS Raw sewage submersible pump for Restaurants, hotels, camp sites etc, Quality Grinder mechanism 440c alloy stainless steel, alloy carbon silicon seals, 304 stainless steel lifting handle for easy removal, 304 stainless steel shaft, stainless steel clamps and quality cast iron body housing HT250. Single Phase, 220v-240 volt 16 meter head, 1.2KW, 7M3/H, 2900 RPM

Installation depth upto a maximum of 10 meters below waste fluid.

[Read More](#)

SKU: SP1612

Price: £780.00 Inc. VAT

Categories: [Sewage Grinder Pumps](#), [Sewage Sump Pumps and Pumping Stations](#)

Product Description

Commercial Grade Sewage sump pump WQAS These pumps are designed for pumping raw sewage from Restaurants, hotels, camp sites etc, Powerful grinder system capable of evacuating waste from multiple washroom appliances via a sump. Quality Grinder mechanism 440c alloy stainless steel, alloy carbon silicon seals, 304 stainless steel lifting handle for easy removal, 304 stainless steel shaft, stainless steel clamps and quality cast iron body housing HT250. Single Phase, 220v-240 volt 16 meter head, 1.2KW, 7M3/H, 2900 RPM Submersible Installation depth upto a maximum of 10 meters below waste fluid.



Commercial Grade Sewage Sump Pump Wqasd7 12-0-9

Commercial Grade Sewage sump pump WQAS Raw sewage pump suitable for installation in restaurants, hotels, camp sites etc, Quality Grinder mechanism 440c alloy stainless steel, alloy carbon silicon seals, 304 stainless steel lifting handle for easy removal, 304 stainless steel shaft, stainless steel clamps and quality cast iron body housing HT250. Single Phase, 220v-240 volt 12 meter head, 0.9KW, 7M3/H, 2900 RPM Installation depth upto a maximum of 10 meters below waste fluid.

[Read More](#)

SKU: SP1209

Price: £660.00 Inc. VAT

Categories: [Sewage Grinder Pumps](#), [Sewage Sump Pumps and Pumping Stations](#)

Product Description

Commercial Grade Sewage sump pump WQAS These pumps are designed for pumping raw sewage from Restaurants, hotels, camp sites etc, Powerful grinder system capable of evacuating waste from multiple washroom appliances via a sump. Quality Grinder mechanism 440c alloy stainless steel, alloy carbon silicon seals, 304 stainless steel lifting handle for easy removal, 304 stainless steel shaft, stainless steel clamps and quality cast iron body housing HT250. Single Phase, 220v-240 volt 12 meter head, 0.9KW, 7M3/H, 2900 RPM Submersible Installation depth upto a maximum of 10 meters below waste fluid.
