



Uniflo Conceal Complete Wc and Macerator version 2

VERY POPULAR ORDER NOW. LIMITED STOCK

- **Uniflo Conceal Complete Toilet and Macerator set. Version 2**
- **Fits back to wall.**
- **Suitable for connection to your Basin or raised Shower Tray.**
- **Discharge pipework 22mm or 32mm**
- **Pumping distance 5.5m vertical, 70m horizontal**
- **External dimensions 360mm wide, Height 770mm, Depth 720mm**

[Read More](#)

SKU: UMP604

Price: £540.00 Inc. VAT

Categories: [Complete Toilet & Macerator Sets](#), [Macerators](#)

Product Description

UNIFLO conceal complete wC and MACERATOR. Version 2

Uniflo Conceal complete toilet and Macerator fits back to wall. A great quality product complete with Toilet and suitable for connection to a basin or raised shower. Ideal for en-suite and basement conversions, the unit is compact and quiet in operation. The whole system fits neatly back to the wall. The side waste outlet allows the small profile elbow to rotate 360 deg for easy connection to the discharge pipework. Complete with waste pump connection fittings and blanks. Ready assembled for easy installation. Discharge in small bore 22mm or 32mm. . One piece porcelain toilet bowl and cistern. . Soft closing toilet seat. . Fully Automatic. . Low level inlet right, for raised Shower or Basin connection. . Low level inlet left, for raised Shower or Basin connection. . Built in Non-Return valves. . Access panels for easy maintenance. **Please Note Important:** Pallet deliveries can take from 2 to 7 working depending on the service you select as Uniflo Products have to arrange with the freight company your chosen delivery date. **Uniflo will contact you via telephone or email to arrange a convenient day for you to accept the goods as someone has to be there to accept delivery, if we are unable to contact you this may delay your delivery.**

TECH SPECIFICATION

Rated voltage 230/240v. Rated power 400 watt. Flow rate Input 12.5 litres per min. Output Flow 145 litres per min. Max water temperature 1Deg C to 50Deg C Dual Stainless steel cutting blades. Air Pressure switch activation GS & CE Certificate.
