



Uniflo Utility Plus Grey Water Pump

- **Uniflo Utility Plus Slim Grey Water Pump.**
- **Suitable for Kitchen Sink, Washing Machine, Basin Shower or Bath.**
- **Discharge pipework 32 mm**
- **Pumping distance 5.5 m vertical, 80 m horizontal**
- **External dimensions 401 mm wide, Height 306 mm, Depth 154 mm**

[Read More](#)

SKU: UMP734

Price: £235.00 Inc. VAT

[Domesetic Utility & Waste Disposal Pumps, Kitchen](#)

Categories: [Appliance Pumps, Kitchen Sink Pumps & Waste Disposal Units, Macerators](#)

Product Description

Uniflo Utility grey water pump fantastic quality product suitable for the installation of a Kitchen sink, Shower & Basin Washing Machine (32 mm discharge only) Bath (32 mm discharge only). Ideal for basement conversions because the slim unit is compact but very quiet in operation. As a result Ideal for new installations also great to replace existing Saniflo Sanivite. Uniflo Utility plus Slim grey water pump body measures Only 135 mm in depth, allowing the unit to easily fit in a under sink cupboard. The top center waste outlet allows the discharge elbow to rotate 360 deg for easy connection to your new or existing discharge pipework. Complete with waste pipe connection fittings and blanks. Discharge in small bore 21.5 mm overflow pipework as well as 22 or 32 mm solvent weld and copper pipe. Self venting because of the internal carbon filter within the unit. Powerful motor of 450 watt.

TECHNICAL INFORMATION

. The unit activates fully automatically as soon as a water source is used. . Top Centre Waste inlet with 360d rotating discharge elbow making it easy to connect either to the right or to the left of the unit. . Ultra low level inlet to the right and left hand side, ideal for shower, basin and kitchen sink connection. . Built in Non-Return valves in both left and right hand side internal tank spigots . Drain off plug. This is ideal for maintenance work that may need to be carried out or when the unit is to be left idle for long periods of time. . Access panels for easy maintenance and access to serviceable parts. . Very easy installation because the unit is supplied with all the specialist parts and fittings so you will be able you to install with minimum fuss. . Slim pump for new installations or to replace your existing Saniflo or Grundfos Macerator.

TECHNICAL SPECIFICATION

Size: Body Depth 135 mm ex lid, Length 383 mm ex inlets, Height 306 mm ex discharge elbow Rated voltage 230/240v. Rated power 450 watt. Flow rate Input 25 liters per min and output Flow is 145 liters per min. Micro switch operation therefore low level pumping Maximum water temperature 40 °C (max 5 minutes 65 °C) GS & CE Certificate. Support and installation <https://unifloproducts.co.uk/support-installation/>
FAQ <https://unifloproducts.co.uk/faqs/>