



# Uniflo Universal Pro 22mm Discharge Macerator Pump

- **Uniflo Universal Pro Macerator Pump.**
- **Unique Macerator with Left or Right discharge outlet.**
- **Suitable for Toilet Shower & Basin**
- **Discharge pipework 22mm or 32mm**
- **Pumping distance 5.5m Vertical, 80m Horizontal**
- **External dimensions 434mm wide, Height 307mm, Depth 165mm**

[Read More](#)

**SKU:** UMP622

**Price:** £198.00 Inc. VAT

**Categories:** [Domestic Macerators](#), [Macerators](#)

## Product Description

**UNIFLO UNIVERSAL PRO 22mm discharge MACERATOR PUMP.** Uniflo Universal is a quality unit, 22 or 32mm discharge Ideal for use with a WC, Basin and Shower, unique in design allowing the installer to attach the discharge outlet to either the left or right side of the unit, this can be vertical and horizontal. Ideal for most installations i.e. en suite bedroom, under stairs and basement conversions the unit is compact and quiet in operation. Replace an existing Saniflo Macerator. The Macerator is also suitable for a stand-alone system for a toilet or toilet and basin. The unit is supplied with built-in non-return valves and a small low-profile elbow and flexible fitting pack for easier installation. Complete with multiple inlet access on both sides, two on top and ultra-low-level bottom inlets on either left or right. The unit is fully automatic and operates when the toilet is flushed, or a basin or shower is used. Practical and modern in design, ideal to convert your basement or loft space into an en suite or shower room. Sensibly Priced. Fully Automatic. Practical Design. Very Easy to Install. Access to help and advice available on our local support line. **Uniflo Universal Pro 22mm Discharge Macerator Pump Specifications and Technical Data.** Height: 307mm x Depth: 165mm x Width: 434. Power: 400w, Electrical Supply 220-240v, 50Hz. Flow Rate: 145L/min. Motor RPM 2800 Vertical Discharge: max-height 5.5 meters Horizontal Discharge: max 85 Meters Dual Stainless-steel cutting System Micro Switch Operation Water Temperature 1 deg c to max 50deg c. IP rating IPX4.